

DECLARATION OF PERFORMANCE No. 00005-DOP-2024/01/24

- 1. Unique Product Type Identification Code: 137 Classic Smooth
- 2. Intended use: Terrace profile for floor structures of external terraces
- 3. Producer: WPC WOODPLASTIC, a.s. V Celnici 1034/6, 110 00 Prague 1, Czech Republic
- 4. POSV Systems: System 3 and System 4
- 5. European Assessment Document: EAD No. 190005-00-0402:2017, European Technical Assessment: ETA No. 23/0919 of 22/12/2023, issued by the Technical and Testing Institute for Construction Prague, s.p. (TZUS)

6. Characteristics declared:

| Basic characteristics | Property | Harmonized technical specification |
|--|---------------------------------------|------------------------------------|
| Reaction to fire | Cfl-s1 | EAD 190005-00- 0402 |
| Swelling in thickness | 2,4 % | |
| Water absorption | 3 % | |
| Bending strength | 28.6 MPa | |
| Modulus of elasticity | 5114 Mpa | |
| Impact strength | 20 J – pass | |
| Creep factor | NPD | |
| Slipperiness Dry (parallel/perpendicular) | 72/85 | |
| Slipperiness Wet (parallel/perpendicular) | 57/65 | |
| Pull-through strength of the fasteners | 2.71 MPa | |
| Moisture resistance under cyclic conditions | 6,0 % | |
| (decrease in strength and modulus of elasticity) | 14,1 % | |
| UV radiation resistance – before ageing | 2.58 kJ/m2 | |
| after ageing(1000h) | 2.61 kJ/m2 | |
| Thermal expansion +30 to +80 °C | 2,57*10 ⁻⁵ K ⁻¹ | |
| Termite resistance | ŅPD | |
| Surface hardness | 63 N/mm2 | |
| Density | 1,21-1,24 g/cm3 | |
| Thermal conductivity | 0,072 W/(m*K) | |

The properties of the above-mentioned product are in accordance with the set of declared properties. In accordance with Regulation (EU) No. 305/2011, this declaration of performance is issued under the sole responsibility of the manufacturer listed above. Signed for and on behalf of the manufacturer:

Bukovany 24/1/2024

WPC - WOODPLASTIC a.s.

V Calaici 1034/6, 110 00 Praha 1

Ing. Jiří Hegr Technologičů: 08920354 0ič: C208920354 ④

